

SHANDONG HAOLONG INTERNATIONAL TRADE CO., LTD.



Name	Project	Product 1
Technical Parameters	Name	Fixed boarding ramp
	Model	HL-GD-8A
	Platform size (mm)	2000*2000mm (length*width)
	Overall dimensions (mm)	2000*2000*600 (length*width*height)
	Working range	+400/-300
	Drive power (v)	380v external power supply (Can be selected according to customer's on-site power supply)
	Motor power (kw)	1.1kw
	Hydraulic system origin	Domestic
	Main seal origin	Germany, Japan
	Electrical system	Delixi
	Control method	Fully electric button control (for fixed boarding ramp only)
	Panel	6mm patterned steel plate
	Main beam	60*120*3mm*8 rectangular tubes
	Base	Front 50*100*3mm/80*4mm manganese steel rectangular tube mixed frame Rear 80*80*4mm Column; 70*70*3mm*6 pieces + 80*80 angle steel
	Overlap tongue plate	16mm patterned steel plate
	Cylinder	80-45; 40-25 each one
	Anti-collision block	Two sets as standard (300*200*100mm)
	Surface treatment	Shot blasting machine grinding and rust removal
	Paint	Paint (spray treatment)
	color	Blue or gray (customizable color)
	Installation method	Pit fixing
	Shipping dimensions (mm)	2000*2000*600 (length*width*height)
	Shipping accessories	Expansion screws; leveling pads; control box fixing screws; welding rods;