

Mobile ramps

10 ton mobile loading and unloading ramp configuration list:

1	Specifications and models	HL-YD-10T
2	Overall dimensions	11300mm (length)*2100mm (width)*1100mm (height)
3	Countertop size	Slope length: 7150mm (length), plane length: 3000mm (length) Rear pedal length: 750mm, front pedal size: 400mm Internal width of equipment: 2000mm, covered with 4mm steel plate and 8mm expanded steel mesh
4	Rated load-bearing	10T
5	Equipped with power	Manual hydraulic pump, 2 hand-cranked legs, leg stroke 400mm
6	Adjustment range	1100-1800mm (equipment adjustment range)
7	Guardrail	200mm (100*50*3) rectangular tube
8	Main structure	160*80*4 rectangular tube 120*60*4 rectangular tube 5 main beams (the distance between cross braces must be about 40 cm)
9	Sub-frame structure	100*50*3mm rectangular tube
10	Hydraulic cylinder	$\Phi 80 * \Phi 45$ (2 pieces)
11	Hydraulic oil pipe	32Mpa high pressure oil pipe
12	Moving rubber wheels	600-9 solid tire
13	bridge and container	The bridge body is welded with hooks and fixed with steel chains.
14	color	medium blue
15	surface treatment	Shot blasting machine grinding and rust removal
16	appendix	Drawbar, tire block,, trailer chain

Mobile ramps

10 ton mobile loading and unloading ramp configuration drawing:

