

## Mobile ramps

### 12ton mobile loading and unloading ramp configuration list:

1	Specifications and models	HL-YD-12T
2	Overall dimensions	11300mm (length)*2100mm (width)*1100mm (height)
3	Countertop size	Slope length: 7150mm (length), plane length: 3000mm (length) Rear pedal length: 750mm, front pedal size: 400mm Internal width of equipment: 2000mm, covered with 5mm steel plate and 8mm expanded steel mesh
4	Rated load-bearing	12T
5	Equipped with power	Manual hydraulic pump, 2 hand-cranked legs, 2 auxiliary legs leg stroke 400mm
6	Adjustment range	1200-1800mm (equipment adjustment range)
7	Guardrail	200mm (40*80*3mm rectangular tube)
8	Main structure	100*200*4 rectangular tube, 5 main beams (the distance between cross braces must be about 40 cm)
9	Sub-frame structure	120*60*4MM rectangular tube
10	Hydraulic cylinder	$\Phi 80 * \Phi 45$ (2 pieces)
11	Hydraulic oil pipe	32Mpa high pressure oil pipe
12	Moving rubber wheels	700-9 solid tire
13	bridge and container	The bridge body is welded with hooks and fixed with steel chains.
14	color	medium blue
15	surface treatment	Shot blasting machine grinding and rust removal
16	appendix	Drawbar, tire block, trailer chain

## Mobile ramps

12 ton mobile loading and unloading ramp drawings:

