

Mobile ramps

15 ton folding mobile loading and unloading ramp configuration list:

1	Specifications and models	HL-YD-15T
2	Overall dimensions	11300mm (length)*2100mm (width)*1100mm (height) Folded length: 5750mm
3	Countertop size	Slope length: 7150mm (long), flat length: 3000mm (long) Rear pedal length: 750mm, front pedal size: 400mm Inner width of equipment: 2000mm, covered with 6mm steel plate and 8mm steel plate mesh
4	Rated load-bearing	15T
5	Equipped with power	Manual hydraulic pump, 2 hand-cranked outriggers, 2 auxiliary outriggers, outrigger stroke 400mm
6	Adjustment range	1200-1800mm (equipment adjustment range)
7	Guardrail	300mm (100*50*4mm rectangular tube)
8	Main structure	100*200*5 rectangular tube, 5 main beams (the distance between cross braces must be about 40 cm)
9	Sub-frame structure	120*60*5mm rectangular tube
10	Hydraulic cylinder	Φ80*Φ45 (2 pieces)
11	Hydraulic oil pipe	32Mpa high pressure oil pipe
12	Moving rubber wheels	700-9 solid tire
13	bridge and container	Hooks are welded on the bridge body and fixed with steel chains
14	color	medium blue
15	surface treatment	Shot blasting machine grinding and rust removal
16	appendix	Drawbar,trailer chain

Mobile ramps

15 ton foldable mobile loading and unloading ramp drawing:

